



## Deck & Fence Formula

## Technical Data Sheet

March 2013

### TR-Series

#### Description

Timber Pro Deck & Fence Natural Oil Wood finish is a premium exterior wood finish formulated with a unique blend of natural oils and resins. Deck & Fence Formula utilizes a unique formula which gives ultimate penetration into the wood. Deck and Fence formula not only accentuates the natural beauty of the wood but it also provides u protection against the damaging UV rays from the sun and destructive effects of the elements.

#### Where to Use

Timber Pro Deck and Fence Formula can be used on all new and reconditioned exterior wood. The Deck and Fence formula can be used on all wood species such as cedar, fir , pine ,cypress, redwood, spruce and pressure treated wood. The following are areas of use for the Deck and Fence Formula.

- Decks
- Fences

#### RESTRICTIONS

- Do not thin
- Do not apply over previously coated surfaces

#### Features and Benefits

- Low V.O.C.
- Excellent UV protection
- Excellent weathering properties
- Large color range
- Easy soap and water cleanup

# Deck & Fence Formula

Technical Data Sheet  
March 2013

## TR-Series

### Color Range and Packaging

**Color :**

(TR series ) Transparent

25 colors available

**Packaging:** 1 US Gallon  
5 US gallon Pail

### Properties

<b>Viscosity -</b>	20-23 secs Zahn cup #2
<b>Gloss Level -</b>	Satin 25-35 GU @ 60 degree
<b>Solids by Weight -</b>	17.8 % +/- 1%
<b>Solids by Volume -</b>	18.1% +/- 1%
<b>V.O.C. -</b>	92 g/l minus water
<b>Weight per gallon-</b>	8.49 lbs./Gal.
<b>Specific Gravity-</b>	1.02
<b>Dry Time -</b>	2-4 touch dry 16 hours through dry for heavy traffic Note dry times will be extended at low temperatures and high humidity

### Shelf Life

Approximately two years in an unopened container

**KEEP FROM FREEZING**

### Coverage

Smooth Wood: 300-400 square feet per gallon

Rough Wood : 150 – 200 square feet per gallon

Hardwoods: 400-450 square feet per gallon

Note : Coverage will vary with the porosity of the wood

# Deck & Fence Formula

## Technical Data Sheet

March 2013

### TR-Series

#### Application

Use a spray applicator , nylon polyester brush or paint pad

#### Clean Up

With soap and mild detergent

#### Product Disclaimer

The technical information and suggestions for use herein are based on Timber Pro Coatings Ltd research and experience and believed to be reliable. But such information and suggestions do not constitute a warranty. Since Timber Pro Coatings has no control over the conditions under which the product is transported, stored, handled, used or applied, buyers must determine for themselves by preliminary tests or otherwise the suitability of the product for their purposes.

#### **Timber Pro Coatings Ltd**

#140-12051 Horseshoe Way, Richmond, BC V7A 4V4  
Ph: 604-270-4244 Fax: 604-270-4247 Toll Free: 1-877-666-4244  
Email: [canadainfo@timberprocoatings.com](mailto:canadainfo@timberprocoatings.com)