



Safety Data Sheet according to Canadian HPR (WHMIS 2015)

1. Identification

1.1. Product identifier

Code: **OP384**
 Product name: **CLEAR SB PU HC TOP COAT 40G**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **Paint for wood**

Identified Uses	Industrial	Professional	Consumer
Pertinent description of use:	✓	✓	-
Uses Advised Against			
Do it yourself			

1.3. Details of the supplier of the safety data sheet

Name: **INDUSTRIA CHIMICA ADRIATICA S.P.A.**
 Full address: **Via S. Pertini, 52**
 District and Country: **62012 Civitanova Marche (MC) ITALY**
 Tel: **+39 0733 8080**
 Fax: **+39 0733 808140**

e-mail address of the competent person responsible for the Safety Data Sheet: **regulatoryaffairs@icaspa.com**

Product distribution by: **INDUSTRIA CHIMICA ADRIATICA S.p.A.**

1.4. Emergency telephone number

For urgent inquiries refer to: **Anti-poison centre – Hospital of Florence (24/24 hours)**
Telephone +39 055 794 7819

2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in Canada's Hazardous Products Regulations (HPR) (WHMIS 2015). The product thus requires a safety datasheet. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Classification and Hazard Statement

Flammable liquid, category 2
 Aspiration hazard, category 1
 Specific target organ toxicity - repeated exposure, category 2

Eye irritation, category 2
 Skin irritation, category 2
 Specific target organ toxicity - single exposure, category 3

Highly flammable liquid and vapour.
 May be fatal if swallowed and enters airways.
 May cause damage to organs through prolonged or repeated exposure.
 Causes serious eye irritation.
 Causes skin irritation.
 May cause respiratory irritation.

Hazard pictograms:



Signal words: **Danger**

Hazard statements:

H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H373 May cause damage to organs through prolonged or repeated exposure.
H319 Causes serious eye irritation.

**2. Hazards identification** ... / >>

H315 Causes skin irritation.
H335 May cause respiratory irritation.

Precautionary statements:

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof [electrical / ventilating / lighting / . . .] equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P260 Do not breathe dust / fume / gas / mist / vapours / spray.
P261 Avoid breathing dust / fume / gas / mist / vapours / spray.
P264 Wash the hands thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves / eye protection / face protection.

Response:

P301+P310 IF SWALLOWED: immediately call a POISON CENTER or doctor.
P302+P352 IF ON SKIN: wash with plenty of water and soap.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 Call a POISON CENTRE / doctor / . . . if you feel unwell.
P314 Get medical advice / attention if you feel unwell.
P331 Do NOT induce vomiting.
P332+P313 If skin irritation occurs: Get medical advice / attention.
P337+P313 If eye irritation persists: Get medical advice / attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P370+P378 In case of fire: use chemical powder to extinguish.

Storage:

P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents and container in accordance with local, regional, international regulations.

2.2. Other hazards

Additional hazards
Information not available

3. Composition/information on ingredients**3.1. Substances**

Information not relevant

3.2. Mixtures

Contains:

Identification x = Conc. % (w/w) Classification:

Xylene, mixture of isomers

CAS 1330-20-7 30 ≤ x < 50

Flammable liquid, category 3 H226, Acute toxicity, category 4 H312, Acute toxicity, category 4 H332, Aspiration hazard, category 1 H304, Specific target organ toxicity - repeated exposure, category 2 H373, Eye irritation, category 2 H319, Skin irritation, category 2 H315, Specific target organ toxicity - single exposure, category 3 H335

N-butyl acetate

CAS 123-86-4 9 ≤ x < 10

Flammable liquid, category 3 H226, Specific target organ toxicity - single exposure, category 3 H336

Butanone

ETHYL METHYL KETONE

CAS 78-93-3 1 ≤ x < 5

Flammable liquid, category 2 H225, Eye irritation, category 2 H319, Specific target organ toxicity - single exposure, category 3 H336

**3. Composition/information on ingredients** ... / >>**Ethyl acetate**CAS 141-78-6 $1 \leq x < 5$ **Flammable liquid, category 2 H225, Eye irritation, category 2 H319,
Specific target organ toxicity - single exposure, category 3 H336**

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

4. First-aid measures**4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

5. Fire-fighting measures**5.1. Extinguishing media**

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

6. Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.



6. Accidental release measures ... / >>

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. If the product is flammable, use explosion-proof equipment. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

UOP U.S.A. Occupational Exposure Limits - Limits for Air Contaminants TABLE Z-1-1910.1000.
 EU OEL EU Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.

Xylene, mixture of isomers

Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
OEL	EU	221	50	442	100	SKIN
OSHA	USA	435	100			

Butanone

Threshold Limit Value					
Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
OEL	EU	600	200	900	300
OSHA	USA	590	200		

Ethyl acetate

Threshold Limit Value					
Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
OEL	EU		400		
OSHA	USA	1400	400		

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.



8. Exposure controls/personal protection ... / >>

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must comply with current regulations.

HAND PROTECTION

Protect hands with category III work gloves (OSHA 29 CFR 1910.138).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear. Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133, CSA Standard CAN/CSA-Z94.3-92).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose class must be chosen according to the limit of use concentration (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134, CSA Standard Z94.4-02). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84, OSHA 29 CFR 1910.134, CSA Standard Z94.4-02.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	liquid	
Colour	opalescent	
Odour	characteristic	
Odour threshold	Not available	
pH	Not available	
Melting point / freezing point	Not available	
Initial boiling point	> 126 °C	(258,8 °F)
Boiling range	Not available	
Flash point	-18 ≤ T ≤ 23 °C	(-0,4 ≤ T ≤ 73,4 °F)
Evaporation Rate	Not available	
Flammability of solids and gases	Not available	
Lower inflammability limit	Not available	
Upper inflammability limit	Not available	
Lower explosive limit	Not available	
Upper explosive limit	Not available	
Vapour pressure	Not available	
Vapour density	> 1,0000	
Relative density	0.97	
Solubility	partially soluble	
Partition coefficient: n-octanol/water	Not available	
Auto-ignition temperature	Not available	
Decomposition temperature	Not available	
Viscosity	Not available	
Explosive properties	Not available	
Oxidising properties	Not available	

9.2. Other information

Total solids (250°C / 482°F)	44,21 %	
VOC :	541.17	g/litre

10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability



10. Stability and reactivity ... / >>

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

Xylene, mixture of isomers

LD50 (Oral)	4300 mg/kg Rat
LC50 (Inhalation)	5000 ppm/4h Rat

Ethyl acetate

LD50 (Oral)	4934 mg/kg Rat
LD50 (Dermal)	> 20000 mg/kg Rabbit
LC50 (Inhalation)	> 22.5 mg/l/6h Rat

N-butyl acetate

LD50 (Oral)	10760 mg/kg Rat
LD50 (Dermal)	> 14112 mg/kg Rabbit
LC50 (Inhalation)	> 20 mg/l/4h Rat

Butanone

LD50 (Oral)	2193 mg/kg Rat
LD50 (Dermal)	> 5000 mg/kg Rabbit
LC50 (Inhalation)	4000 ppm Rat

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION



11. Toxicological information ... / >>

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

Carcinogenicity Assessment:

1330-20-7	Xylene, mixture of isomers IARC:3
100-41-4	Ethylbenzene IARC:2B
64-17-5	Ethanol IARC:1

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause respiratory irritation

STOT - REPEATED EXPOSURE

May cause damage to organs

ASPIRATION HAZARD

Toxic for aspiration

12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

Xylene, mixture of isomers

LC50 - for Fish 13.4 mg/l/96h Fish

EC50 - for Crustacea 8.5 mg/l/48h

Ethyl acetate

LC50 - for Fish 230 mg/l/96h Fish

EC50 - for Crustacea 165 mg/l/48h Daphnia magna

Chronic NOEC for Crustacea 2.4 mg/l Daphnia pulex

N-butyl acetate

LC50 - for Fish 18 mg/l/96h Fish

EC50 - for Algae / Aquatic Plants 397 mg/l/72h Alga

**12. Ecological information** ... / >>

Butanone

LC50 - for Fish 2993 mg/l/96h Fish

EC50 - for Crustacea 308 mg/l/48h Daphnia

12.2. Persistence and degradabilityXylene, mixture of isomers
Rapidly degradableEthyl acetate
Rapidly degradableN-butyl acetate
Rapidly degradableButanone
Rapidly degradable**12.3. Bioaccumulative potential**Xylene, mixture of isomers
LogPow: 3.12.
BCF: 8.1 to 25.9.
Potential: Low.**12.4. Mobility in soil**

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

14. Transport information**14.1. UN number**

ADR / RID, IMDG, IATA: 1263

14.2. UN proper shipping nameADR / RID: PAINT
IMDG: PAINT
IATA: PAINT



14. Transport information ... / >>

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3



IMDG: Class: 3 Label: 3



IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA: II

14.5. Environmental hazards

ADR / RID: NO

IMDG: NO

IATA: NO

14.6. Special precautions for user

ADR / RID: HIN - Kemler: 33
Special Provision: 640C

Limited Quantities: 5 L

Tunnel restriction code: (D/E)

IMDG: EMS: F-E, S-E

Limited Quantities: 5 L

IATA: Cargo:

Maximum quantity: 60 L

Packaging instructions: 364

Pass.:

Maximum quantity: 5 L

Packaging instructions: 353

Special Instructions:

A3, A72, A192

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Substances subject to the Rotterdam Convention:
None

Canadian Regulatory Information

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR).

Safety Data Sheet according to WHMIS 2015.

Inventory Status of the contained substance/s.

All ingredients are listed in DSL.
MAL Code: 4-3

16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H319	Causes serious eye irritation.



16. Other information ... / >>

H315	Causes skin irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CLP: EC Regulation 1272/2008
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

GENERAL BIBLIOGRAPHY:

- GHS rev. 5
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh - Registry of Toxic Effects of Chemical Substances
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

- Hazard Products Regulation (HPR)
- WHMIS 2015
- ONTARIO R.R.O. 1990, Regulation 883 (version July 2016)
- IARC website
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.