

Technical Data Sheet NR 7266

SLOW POLYURETHANE THINNER

Creation date: 25/05/1998 Revision date: 29/11/2006, version 1

ICA S.p.a. Via S. Pertini n. 52, Zona Ind.le A 62012 Civitanova Marche (MC) - Italy
Tel. +39 0733 8080 Fax. +39 0733 808140

PRODUCT: D1015 SLOW POLYURETHANE THINNER

DESCRIPTION: D1015 is a polyurethane thinner with excellent solvent power and an extremely slow evaporation curve, and is therefore suitable for polyurethane top coats in hot weather or whenever it is necessary to slow down drying times of the top coats.

SPECIFICATIONS OF SUPPLIED PRODUCT

SHELF LIFE AT 20°C: 24 months in correctly stored unopened tin

SPECIFICATIONS OF SUPPLIED PRODUCT	CHARACTERISTICS	UNITS	VALUE	METHOD
	Specific gravity at 20°C:	g/ml	0.89 ± 0.05	MP01

Always verify the suitability of the product for the job to be done before application. We can not accept responsibility for the outcome.

The information contained in this technical data sheet, as well as any verbal information, is given to the best of our knowledge. We do not accept responsibility for obsolete or incorrect information. The information is to be considered obsolete when a new technical data sheet is issued. Please feel free to contact us to request the latest edition.

D1015/1

Pagina 1 di 1