



Log and Siding Formula

Technical Data Sheet

March 2013

Clear

TR-Series

ST-Series

SS-Series

Description

Timber Pro Log and Siding formula Natural Oil Wood finish is a premium exterior wood finish formulated with a unique blend of natural oils and resins. Log and Siding Formula not only accentuates the natural beauty of the wood but it also provides unsurpassed protection against the damaging UV rays from the sun and destructive effects of the elements.

Where to Use

Timber Pro Log and Siding Formula can be used on all new and reconditioned wood exterior and interior surfaces. The Log and siding formula can be used on all wood species such as cedar, fir, pine, cypress, redwood, spruce exterior grade plywood and pressure treated wood. The following are areas of use for the Log and Siding Formula.

- log Homes
- exterior sidings
- decks
- shingles
- shakes
- fences
- trim
- doors/windows
- planters
- outdoor furniture

RESTRICTIONS

Always use a color from one of the color series before using the clear

- Do not use clear alone for exterior surfaces
- Do not thin
- Do not apply over previously coated surfaces

Features and Benefits

- Can be used in interior and exterior wood surfaces
- Low V.O.C.
- Excellent UV protection
- Excellent weathering properties
- Large color range
- Easy soap and water cleanup

Log and Siding Formula

Technical Data Sheet
March 2013

Clear **TR-Series** **ST-Series** **SS-Series**

Color Range and Packaging

Color : Clear

(TR series)	Transparent	24 colors available
(ST series)	Semi Transparent	18 colors available
(SS series)	Semi Solid	14 colors available

Packaging: 1 US Gallon
 5 US gallon Pail

Properties

Viscosity -	20-23 secs Zahn cup #2
Gloss Level -	Satin 25 - 35 GU @ 60 degree
Solids by Weight -	23.2 % +/- 1%
Solids by Volume -	22.5% +/- 1%
V.O.C. -	93.6 g/l minus water
Weight per gallon-	8.45 lbs./Gal.
Specific Gravity-	1.01
Dry Time -	2-4 touch dry 16 hours through dry Note dry times will be extended at low temperatures and high humidity

Shelf Life

Approximately two years in an unopened container

KEEP FROM FREEZING

Coverage

Smooth Wood: 250-300 square feet per gallon

Rough Wood : 150 – 200 square feet per gallon

Hardwoods: 300-400 square feet per gallon

Note : Coverage will vary with the porosity of the wood

Log and Siding Formula

Technical Data Sheet
March 2013

Clear

TR-Series

ST-Series

SS-Series

Application

Use a spray applicator , Roller or nylon polyester brush

Clean Up

With soap and mild detergent

Product Disclaimer

The technical information and suggestions for use herein are based on Timber Pro Coatings Ltd research and experience and believed to be reliable. But such information and suggestions do not constitute a warranty. Since Timber Pro Coatings has no control over the conditions under which the product is transported, stored, handled, used or applied, buyers must determine for themselves by preliminary tests or otherwise the suitability of the product for their purposes.

Timber Pro Coatings Ltd

#140-12051 Horseshoe Way, Richmond, BC V7A 4V4
Ph: 604-270-4244 Fax: 604-270-4247 Toll Free: 1-877-666-4244
Email: canadainfo@timberprocoatings.com