



VINYL ACRYLIC DRYWALL PRIMER 4100 SERIES TECHNICAL DATA

A premium quality full bodied latex primer and sealer that provides excellent coverage and an uniform seal for plaster, drywall and previously painted surfaces. Used in the home, office, institutional, and industrial applications. Available in white and upon request pastel colours.

SPECIFIC GRAVITY: 1.6

FLASH POINT: NONE

GLOSS: < 5 @ 60°

VISCOSITY: 100-105 KU

AGRICULTURE CANADA: Approved for food storage.

SURFACE PREPARATION:

All surfaces should be clean, dry and free of dust, grease, wax or other contaminants. Previously painted surface should be scrapped, cleaned and repaired where necessary with a spackling compound to ensure a smooth, sound surface before applying paint. Dull glossy surfaces by fine sandpaper. Prime where necessary. Shellac all knots and prime bare wood with an oil-based primer. Plaster must age at least 30 days and be thoroughly dry before painting.

APPLICATION: Apply at air temperature of 10 C or higher. May be applied by brush, roller, or spray.

Stir product with a circular, lifting motion prior to using the product. Brush a 4-foot section on the edges and roll in the middle using “W’s” or “M’s”. Fill in the section and always finish on the down stroke from the very top of the wall to the very bottom in one clean motion. Overlap slightly and continue until the wall is finished.

Brush-Nylon or Polyester is sleeve is recommended.

Spray- (Airless Equipment) - .015" to .019" tip size.

- 2300-2700 p.s.i.

*Spray recommendations will vary according to manufacturer.

DRY TIME: Dry to touch 30 minutes. Recoat 2-4 hours.

SPREADING RATE: Up to 240 Sq.ft/4 litres on bare surfaces.

Up to 440 Sq. ft/ 4 litres yields approx. 4 mils wet (2.0 mils dry) film per coat on sealed surface. Surface texture and porosity will affect actual yield.

CLEAN UP: Use warm soapy water to wipe spots and smears immediately and to clean tools.

THINNING: Not normally recommended but water if necessary.