



335 Horner Avenue, Toronto, Ontario M8W 1Z6  
 Canada Ph (416) 251-0051 fx (416) 251-3412  
 www.protekpaint.com

## SAFETY DATA SHEET

### SECTION 1: IDENTIFICATION

**Product Code:** MC416G  
**Product Trade Name:** 2900 Traditions Pearl Alkyd Emulsion Pastel Base  
**Product Class / Intended End Use:** Architectural Coating  
**Emergency Telephone Numbers:** For emergency health, safety and environmental information call 416-252-5676 (Monday to Friday 9am-4pm est/edt)

**For Emergency Transportation Information call CANUTEC at 613-996-6666**

### SECTION 2: HAZARDS IDENTIFICATION

**Classification:**

	Category
Aquatic, Acute	3
<b>Signal word:</b>	<b>WARNING</b>

**Hazard Statements:**

- Harmful to aquatic life

**Precautionary Statements:**

- Dispose of contents/container to hazardous or special waste collection point

**Other Hazards not Classified:**

- None known

**Hazard Pictograms:**



### SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS #	WT %
Alcohols, C12-14, ethoxylated, sulfates, sodium salts	68891-38-3	1.8
<i>N/A = Not Available N/E = Not Established</i>		

# PROTEK PAINT – SAFETY DATA SHEET

## SECTION 4: FIRST-AID MEASURES

<b>Inhalation:</b>	Keep patient calm, remove to fresh air.
<b>Skin Contact:</b>	Rinse skin thoroughly with soap and water.
<b>Eye Contact:</b>	Immediately flush eyes with gentle flowing water for 10-15 minutes.
<b>Ingestion:</b>	Rinse mouth and then drink plenty of water.

*Call a poison centre or doctor/physician if you feel unwell.*

### Most Important Symptoms and Effects (both acute and delayed):

- None known

### Indication of any Immediate Medical Attention and Special Treatment Needed:

- Treat symptomatically

## SECTION 5: FIRE-FIGHTING MEASURES

<b>Suitable Extinguishing Media:</b>	Water fog, CO <sub>2</sub> , extinguishing powder, foam.
<b>Unsuitable Extinguishing Media:</b>	Do not use a heavy water stream.
<b>Specific Hazards Arising from the Substance or Mixture:</b>	Harmful vapours, carbon oxides, sulfur oxides. Evolution of fumes/fog.
<b>Special Protective Equipment and Precautions for Fire Fighters:</b>	Move containers from fire area if possible to do without risk. Wear self-contained breathing (SCBA) apparatus and full firefighting protective clothing. Do not use solid water stream as it may scatter and spread the fire.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

<b>Personal Precautions, Protective Equipment and Emergency Procedures:</b>	Use personal protective equipment. Provide adequate ventilation.
<b>Environmental Precautions:</b>	Do not discharge into drains/surface waters/ground water.
<b>Methods and Materials for Containment and Clean Up:</b>	For small amounts: Pick up with absorbent material (e.g. sand, sawdust, general purpose binder). Dispose of absorbed material in accordance with regulations. For large amounts: Pump off product. Spills should be contained, solidified, and placed in suitable containers for disposal.

## SECTION 7: HANDLING AND STORAGE

<b>Precautions for Safe Handling:</b>	Wash hands before eating or drinking.
<b>Conditions for Safe Storage:</b>	Use in a well ventilated area. Exhaust ventilation is recommended if used indoors on a continuous basis. If exposure exceeds occupational limits (TLV value) wear appropriate NIOSH approved air purifying respirator.
<b>Incompatibles:</b>	Acids, strong oxidizers.

# PROTEK PAINT – SAFETY DATA SHEET

## SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Name	ACGIH TLV (ppm)		OSHA PEL (ppm)	
	TWA	STEL	PEL	STEL
Alcohols, C12-14, ethoxylated, sulfates, sodium salts	N/A	N/A	N/A	N/A
<i>N/A = Not Available N/E = Not Established</i>				

**Appropriate Engineering Controls:** Use only in well ventilated areas. Exhaust ventilation if used indoors on a continuous basis.

**Personal Protective Equipment Respiratory Protection:** If exposure cannot be controlled below applicable limits, use the appropriate NIOSH approved respirator such as an air purifying respirator with organic vapour cartridge and dust/mist filter.

**Eye Protection:** Use safety glasses with side shields.

**Skin Protection:** Wear protective clothing as necessary to minimize contact. Handle in accordance with good industrial hygiene and safety practice. No eating, drinking, smoking or tobacco use at the place of work. Handle in accordance with good industrial hygiene and safety practice.

## SECTION 9: PHYSICAL PROPERTIES

<b>% Volatiles by Weight:</b>	41.68
<b>Auto Ignition Temperature:</b>	Data not Available
<b>Boiling Point:</b>	>100 °C / 212 °F
<b>Decomposition Temperature:</b>	Data not Available
<b>Explosive Limit:</b>	Data not Available
<b>Flammability (solid, gas):</b>	Not Flammable
<b>Flash Point (Setaflash Closed Cup):</b>	Not Applicable
<b>Freezing Point:</b>	<0 °C / 32 °F
<b>Melting Point:</b>	Data not Available
<b>Odour Threshold:</b>	Data not Available
<b>Odour:</b>	Slight Sweet
<b>Partition Coefficient:</b>	Data not Available
<b>pH:</b>	8.0 – 9.0
<b>Physical State/Appearance:</b>	Viscous White Liquid
<b>Relative Evaporation Rate (Butylacetate=1)</b>	Data not Available
<b>Solubility in Water:</b>	Miscible
<b>Specific Gravity:</b>	1.34
<b>Vapour Density:</b>	Data not Available
<b>Vapour Pressure:</b>	Data not Available
<b>Viscosity:</b>	Viscous

# PROTEK PAINT – SAFETY DATA SHEET

## SECTION 10: STABILITY AND REACTIVITY

<b>Reactivity:</b>	No hazardous reactions if stored and handled as prescribed/indicated.
<b>Chemical Stability:</b>	Stable at normal condition of usage.
<b>Possibility of Hazardous Reactions:</b>	No hazardous reactions when stored and handled according to instructions.
<b>Conditions to Avoid:</b>	Avoid ignition sources, heat, sparks, open flame, direct sunlight and extremely high or low temperatures.
<b>Incompatibles:</b>	Acids, strong oxidizers. Materials reactive with hydroxyl bearing compounds.
<b>Hazardous Decomposition Products:</b>	No hazardous decomposition products if stored and handled as prescribed/indicated.

## SECTION 11: TOXICOLOGICAL INFORMATION

Name	LD 50			LC 50		
	mg/kg	Animal	Route	ppm	Animal	Route
Alcohols, C12-14, ethoxylated, sulfates, sodium salts	>5000	Rat	Oral		N/A	
<b>N/A = Not Available N/E = Not Established</b>						

<b>Likely Routes of Exposure:</b>	Ingestion and inhalation but may include eye or skin contact.
<b>Symptoms/Injuries after Inhalation:</b>	No
<b>Symptoms/Injuries after Skin Contact:</b>	Direct contact with eyes can cause slight irritation.
<b>Symptoms/Injuries after Ingestion:</b>	May cause gastrointestinal irritation.

## SECTION 12: ECOLOGICAL INFORMATION

<b>Toxicity:</b>	Hazardous to aquatic life.
<b>VOC (g/L):</b>	70
<b>Persistence and Degradability:</b>	No test data on mixture
<b>Bio-accumulative Potential:</b>	No test data on mixture
<b>Mobility in Soil:</b>	No test data on mixture
<b>Other Adverse Effects:</b>	None known

## SECTION 13: DISPOSAL CONSIDERATIONS

<b>Handling for Disposal:</b>	Handle waste according to recommendations in Section 7. Empty containers retain residue (liquid and/or vapour) and can be dangerous. Do not cut, weld, drill or grind on or near this container.
<b>Methods of Disposal:</b>	Dispose of in accordance with federal, provincial/state and local hazardous waste laws. Do not discharge into sewage or municipal water. Do not incinerate closed containers.
<b>RCRA:</b>	If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.

**DO NOT INCINERATE CLOSED CONTAINERS**

# PROTEK PAINT – SAFETY DATA SHEET

## SECTION 14: TRANSPORTATION INFORMATION

<b>UN Number:</b>	Non Regulated
<b>UN Proper Shipping Name:</b>	Non Regulated
<b>Transport Hazard Class:</b>	Non Regulated
<b>Packing Group:</b>	Non Regulated
<b>Environmental Hazards:</b>	Information not available
<b>Special Precautions for User:</b>	Appropriate advice on safety should accompany the package. Do not allow product to enter waterways.
<b>Transport in Bulk:</b>	Information not available.

## SECTION 15: REGULATORY INFORMATION

**Canada:** All components are in compliance with the Canadian environmental protection act and are present on the domestic substances list. This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the CPR.

**USA:**

**TSCA:** All components of this material are on the US TSCA inventory or are exempt.

**OSHA:** This material is classified as hazardous under OSHA regulation (29CFR 1910.1200).

**CERCLA:** Reportable quantities (RQ) (40 CFR 117.302). Data not Available.

**SARA TITLE 111:** Sec 302, extremely hazardous substances, 40 CFR 355 - Data not available

**SARA TITLE 111:** Sec 313, toxic chemical notification, 40 CFR 372 - Data not Available

## SECTION 16: OTHER INFORMATION

<b>HMIS:</b>	Health 1	Flammability 0	Physical hazard 0	
<b>NFPA:</b>	Health 1	Flammability 0	Reactive Instability 0	Special Hazard 0

**Issue Date: April 3, 2017**

**Revision Date: April 3, 2017**

### DISCLAIMER

*While Protek Paint believes that the data contained herein are factual and the opinions expressed are those of qualified experts regarding the results of the tests conducted, the information and data contained herein is not to be taken as warranty or representation for which Protek Paint assumes liability. They are offered solely for your consideration, investigation and verification. Final determination of the suitability of the material for the use contemplated, the manner of use and whether the suggested use infringes any patent is the sole responsibility of the buyer.*

*This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of Protek Paint*

**END OF SAFETY DATA SHEET**