



335 Horner Avenue, Toronto, Ontario M8W 1Z6
 Canada Ph (416) 251-0051 fx (416) 251-3412
 www.protekpaint.com

SAFETY DATA SHEET

Product Code: MC451M
Product Trade Name: Armaglaze 9000 Reducer
Product Class / Intended End Use: Commercial Coating
Emergency Telephone Numbers: For emergency health, safety and environmental information call 416-252-5676 (Monday to Friday 9am-4pm est/edt)

For Emergency Transportation Information call CANUTEC at 613-996-6666

SECTION 2: HAZARDS IDENTIFICATION

Classification:

	Category
Flammable Liquid & Vapour	3
Signal word:	Warning

Hazard Statements:

- Flammable liquid and vapour

Precautionary Statements:

- Keep away from heat / sparks / open flames / hot surfaces. NO SMOKING
- Keep containers tightly closed
- Ground/bond container and receiving equipment
- Use explosion-proof electrical/ventilation/lighting/equipment
- Use only non-sparking tools
- Take precautionary measures against static discharge
- Wear protective gloves/protective clothing/eye protection/face protection
- Store locked up

Other Hazards Which do no Result in Classification:

- None known

Hazard Pictograms:



SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS #	WT RANGE %
2-methoxy-1-methylethyl acetate	108-65-6	100
<i>N/A = Not Available N/E = Not Established</i>		

PROTEK PAINT – SAFETY DATA SHEET

SECTION 4: FIRST-AID MEASURES

Inhalation:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.
Skin Contact:	Take off contaminated clothing. Rinse skin with soap and water. Wash contaminated clothing before reuse. If skin irritation occurs, get medical attention.
Eye Contact:	Immediately flush eyes with gentle flowing water for 10-15 minutes. Remove contact lenses if present and easy to do. Get medical attention.
Ingestion:	Get medical advice/attention.

Call a poison centre or doctor/physician if you feel unwell.

Most Important Symptoms and Effects (both acute and delayed):

- None known

Indication of any Immediate Medical Attention and Special Treatment Needed:

- Treat symptomatically.

SECTION 5: FIRE-FIGHTING MEASURES

Suitable Extinguishing Media:	Water fog, CO ₂ , extinguishing powder, foam.
Unsuitable Extinguishing Media:	Do not use a solid water stream as it may scatter and spread fire.
Specific Hazards Arising from the Substance or Mixture:	None known.
Special Protective Equipment and Precautions for Fire Fighters:	Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. A full-body chemical resistant suit should be worn.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures:	Evacuate personnel to safe areas. Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame. Dike for water control. Avoid release to the environment.
Environmental Precautions:	Ensure spilled product does not enter drains, sewers, waterways, or confined spaces. For large spills, dike the area to prevent spreading.
Methods and Materials for Containment and Clean Up:	Remove all sources of ignition. Ventilate the area. Prevent further leakage or spillage if safe to do so. Dike for water control. Use only non-sparking tools and equipment in the clean-up process. Spilled material will create slippery surfaces. Clean up promptly. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand), then place absorbent material into a container for later disposal (see Section 13). Contact the proper local authorities.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling:	Use only outdoors or in a well-ventilated area. Wear suitable protective equipment. Avoid breathing mist or vapours. Avoid contact with skin, eyes and clothing. Keep away from heat and open flames. - No smoking. Use only non-sparking tools. Use explosion-proof electrical/ventilating/lighting/equipment. Keep away from oxidizing agents. Keep away from incompatibles. Label containers appropriately. Wash thoroughly after handling. Keep containers closed when not in use.
Conditions for Safe Storage:	Keep away from heat, sparks and open flame. - No smoking. Store in a cool, dry, well-ventilated area. Store away from incompatibles and out of direct sunlight. Keep cool. Keep container tightly closed. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks.
Incompatibles:	Strong oxidizers (e.g. Chlorine, Peroxides, etc.).

PROTEK PAINT – SAFETY DATA SHEET

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Name	ACGIH TLV (ppm)		OSHA PEL (ppm)	
	TWA	STEL	PEL	STEL
2-methoxy-1-methylethyl acetate	50	N/A	N/A	N/A
<i>N/A = Not Available N/E = Not Established</i>				

- Control Parameters:** No TLV data available on product.
- Appropriate Engineering Controls:** Provide exhaust ventilation or other engineering controls to keep the airborne concentration of vapours below their respective threshold limit value.
- Personal Protective Equipment**
- Respiratory Protection:** Respiratory protection is required if the concentrations exceed the TLV. Use a NIOSH approved dust respirator if dust levels exceed exposure limits. Seek advice from respiratory protection specialists.
- Eye/Face Protection:** Chemical goggles must be worn to prevent dusts from entering the eyes.
- Other Protective Equipment:** Wear appropriate protective clothing to prevent skin contact, such as coveralls or long sleeved shirt, long pants, and shoes and socks. Wear protective gloves. An eyewash station and safety shower should be made available in the immediate working area. Other equipment may be required depending on workplace standards.
- General Hygiene Considerations:** Avoid breathing mist or vapours. Avoid contact with skin, eyes and clothing. Do not eat, drink, smoke or use cosmetics while working with this product. Upon completion of work, wash hands before eating, drinking, smoking or use of toilet facilities. Remove soiled clothing and wash it thoroughly before reuse.

SECTION 9: PHYSICAL PROPERTIES

% Volatiles by Weight:	100
Autoignition Temperature	Data not Available
Boiling Point:	150 °C / 302 °F
Decomposition Temperature:	Data not Available
Density / Specific Gravity:	0.969
Explosion Limit:	Data not Available
Flammability (solid, gas):	Flammable
Flash Point (Setaflash Closed Cup):	46 °C / 114.8 °F
Melting Point/Freezing Point:	Not Applicable
Odour Threshold:	Data not Available
Odour:	Sharp Sweet
Partition Coefficient:	Data not Available
pH:	Data not Available
Physical State/Appearance:	Clear Liquid
Relative Evaporation Rate (Butylacetate=1)	Data not Available
Solubility in Water:	None
Vapour Density:	Not Applicable
Vapour Pressure:	Not Applicable
Viscosity:	10 – 20 cps

SECTION 10: STABILITY AND REACTIVITY

Reactivity:	Not normally reactive
Chemical Stability:	Stable under normal condition of usage
Possibility of Hazardous Reactions:	Under normal storage and use, hazardous polymerization will not occur.
Conditions to Avoid:	Ensure adequate ventilation, especially in confined areas. Avoid contact with incompatible materials.
Incompatibles:	Strong oxidizers (e.g. Chlorine, Peroxides, etc.).
Hazardous Decomposition Products:	None known, refer to hazardous combustion products in Section 5.

PROTEK PAINT – SAFETY DATA SHEET

SECTION 11: TOXICOLOGICAL INFORMATION

Name	LD 50			LC 50		
	mg/kg	Animal	Route	ppm	Animal	Route
2-methoxy-1-methylethyl acetate	6190 >5,000	Rat Rabbit	Oral Dermal	>4345	Rat	Inhalation, 4h
<i>N/A = Not Available N/E = Not Established</i>						

Acute Toxicity: No test data on mixture.

No Test Data for the Mixture On: Skin corrosion/irritation, eye damage/irritation, skin sensitization, respiratory sensitization, germ cell mutagenicity, carcinogenicity, reproductive toxicity, STOT- single exposure, STOT- repeated exposure, aspiration.

Likely Routes of Exposure: Inhalation, eye contact, skin contact, ingestion.

Symptoms/Injuries after Inhalation: May cause respiratory tract irritation.

Symptoms/Injuries after Skin Contact: May cause mild skin irritation on prolonged contact.

Symptoms/Injuries after Eye Contact: Direct eye contact may cause slight redness.

Symptoms/Injuries after Ingestion: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Potential Chronic Health Effects: None known.

Specific Target Organ Effects: None known.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:	Data not available.
VOC (g/L):	970
Persistence and Degradability:	Not readily biodegradable
Bio-accumulative Potential:	No test data
Mobility in Soil:	Data not available
Other Adverse Effects:	None known

SECTION 13: DISPOSAL CONSIDERATIONS

Handling for Disposal: Handle waste according to recommendations in Section 7. Empty containers retain residue (liquid and/or vapour) and can be dangerous. Do not cut, weld, drill or grind on or near this container.

Methods of Disposal: Dispose of in accordance with federal, provincial/state and local hazardous waste laws. Do not discharge into sewage or municipal water.

RCRA: If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.

DO NOT INCINERATE CLOSED CONTAINERS.

PROTEK PAINT – SAFETY DATA SHEET

SECTION 14: TRANSPORTATION INFORMATION

UN Number:	1263
UN Proper Shipping Name:	Paint
Transport Hazard Class:	3
Packing Group:	III
Environmental Hazards:	Information not available.
Special Precautions for User:	Appropriate advice on safety should accompany the package. Keep away from heat, sparks and open flame. Avoid static electricity.
Transport in Bulk:	Information not available.

SECTION 15: REGULATORY INFORMATION

- Canada:** All components are in compliance with the Canadian environmental protection act and are present on the domestic substances list. This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the CPR.
- USA:**
- TSCA:** All components of this material are on the US TSCA inventory or are exempt.
 - OSHA:** This material is classified as hazardous under OSHA regulation (29CFR 1910.1200).
 - CERCLA:** Reportable quantities (RQ) (40 CFR 117.302). Data not Available.
 - SARA TITLE 111:** Sec 302, extremely hazardous substances, 40 CFR 355 - Data not available
 - SARA TITLE 111:** Sec 313, toxic chemical notification, 40 CFR 372 - Data not Available

SECTION 16: OTHER INFORMATION

HMIS:	Health 2	Flammability 2	Physical Hazards 1
NFPA:	Health 2	Flammability 2	Instability 0

Issue Date: November 21, 2016

Revision Date: November 21, 2016

DISCLAIMER

While Protek Paint believes that the data contained herein are factual and the opinions expressed are those of qualified experts regarding the results of the tests conducted, the information and data contained herein is not to be taken as warranty or representation for which Protek Paint assumes liability. They are offered solely for your consideration, investigation and verification. Final determination of the suitability of the material for the use contemplated, the manner of use and whether the suggested use infringes any patent is the sole responsibility of the buyer.

This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of Protek Paint.

END OF SAFETY DATA SHEET