

Vesuvio plaster

Vesuvio is an eco-friendly, trowel-applied wall-coating obtained from selected carbonates and marble powders and genuine slaked-lime CL 90-S baked in wood-fire kilns and aged for 8-10 months.

It is suitable for indoor applications and allows to obtain relief, rough or smooth surfaces according to the technique.

- one coat of primer **Texprime**
- one coat of **Vesuvio**
- countless possibilities of

COLOR RANGE

Duetto is available in color **Natural White**.

For an even coloring of the base product, clean the pot inner-edge and accurately stir the chosen **Colorants**. Stir the base product, gradually pour the colorant and mix until an homogeneous blend has been reached. It is advisable to let the tinted product rest for at least 12 hours prior to its application.

PREPARATION OF THE SUBSTRATE

A correct preparation of the substrate is of utmost importance for an optimal application result.

Primer **Texprime**, applied by roller or brush.

Texprime, is a white, water-based primer containing extra-fine quartz.

In case of **NEW SURFACES** as traditional concrete, concrete-based plasters, gypsum and plasterboard, apply a coat of primer.

In case of **OLD SURFACES** as plaster, tempera paint and breathable paint in good conditions, it is necessary to brush the surface before applying a coat of primer.

In case of **OLD SURFACES** presenting powdery surface conditions, or that are coated with wax or soap, it is also necessary to sandpaper the surface before applying a coat of primer

APPLICATION CYCLE

Product: **Texprime**

Consumption: **approx. 150 to 200 g/m²** according to surface

The product is ready for use.

Apply a coat by roller or brush.

FIRST COAT

Product: **Vesuvio Natural White** or **colored**

Consumption: **approx. 1200 to 1500 g/m²** according to the desired effect

Remove any excess of water inside the pot before use.

Apply an even first coat. Structure the surface at will, more or less polished, or drawing veins using the Texturing Trowel for a rougher effect.

TOPCOAT

Let the surface dry out for at least 48 hours. According to the applied surface and to the final effect desired, we propose the following topcoats: Cera Naturale,

Savon de Marseille, These can be combined with each other and tinted with Colorant Additives.

Please refer to the relevant data sheets for features and application instructions.

ENVIRONMENTAL CONDITIONS OF APPLICATION

Whenever possible, use the same batch for an entire wall.

Apply the product only over matured and dry mortars.

During application the temperature should be included between +10°C and +30°C, while the relative humidity should be lower than 85% also during the 24 hours following the application.

STORAGE

The product maintains its properties for a period of 24 months if protected from excessive heat and cold.

Storage temperature should be included between +5°C and +30°C.

Protect from frost.

SAFETY GUIDELINES

Avoid contact with skin and eyes. If contact occurs, rinse thoroughly with water.

Keep away from the reach of children.

For more information consult the safety sheet.

DISPOSAL

The product must be disposed in agreement with current regulations.

Empty containers should be sent to recycling plants.

TECHNICAL DATA

Specific weight 1,56 ± 0,05 kg/l

Coating thickness 1,50 mm (minimum)

Dry to the touch 6 hours with 20°C room temperature

Stable hardness 180 days

VOC 0 g/l

Dir. 2004/42/EC Cat. A/c, limit value 2010: 40 g/l