



335 Horner Avenue, Toronto, Ontario M8W 1Z6
 Canada Ph (416) 251-0051 fx (416) 251-3412
 www.protekpaint.com

SAFETY DATA SHEET

SECTION 1: IDENTIFICATION

Product Code: MC415Y
Product Trade Name: Texturbase Accent
Product Class / Intended End Use: Decorative Architectural Coating
Emergency Telephone Numbers: For emergency health, safety and environmental information call 416-252-5676 (Monday to Friday 9am-4pm est/edt)

For Emergency Transportation Information call CANUTEC at 613-996-6666

SECTION 2: HAZARDS IDENTIFICATION

Classification:

	Category
Acute toxicity, oral	4
Inhalations	2
Eye irritation	2B
Signal word:	WARNING

Hazard Statements:

- Harmful if swallowed.
- Harmful if inhaled.
- Causes eye irritation.
- Prolonged or repeated skin contact causes irritation.

Precautionary Statements:

- Keep container tightly closed; store in cool well ventilated area.
- Wear protective gloves, and eye/face protection.
- Do not breathe mist/vapours/spray; use in a well ventilated area.
- Do not eat or drink when using this product; wash hands after using product.
- If swallowed: rinse mouth, call a poison center or doctor if you feel unwell.
- If inhaled: remove person to fresh air; call a poison center or doctor if you feel unwell.
- If in eyes: rinse cautiously with water for several minutes; remove contact lenses if present and easy to do; continue rinsing.
- If on skin; take off immediately all contaminated clothing; rinse skin in water/shower; wash contaminated clothing before reuse.
- If skin irritation occurs; get medical attention.
- Dispose of waste, empty containers in accordance with federal, provincial/state and local hazardous waste laws; do not discharge into sewage or municipal water.

Hazard Pictograms:



PROTEK – SAFETY DATA SHEET

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures:	Use personal protective equipment. If flammable, remove all sources of ignition (flames, sparks, etc.). Provide adequate ventilation. If necessary, evacuate personnel to safe area.
Environmental Precautions:	Try to prevent material from entering drains or water area.
Methods and Materials for Containment and Clean Up:	Small spills should be absorbed with clay, diatomaceous earth or other suitable inert absorbent. Clean up with non-sparking tools. Store spilled material in suitable, closed containers suitable for disposal. Large spills may be pumped into appropriate closed containers for recovery or disposal.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling:	Avoid inhalation, skin and eye contact. Wear personal protective equipment. Handle with good industrial hygiene. Wash hands before eating or drinking.
Conditions for Safe Storage:	Use in a well ventilated area. Exhaust ventilation is recommended if used indoors on a continuous basis. If exposure exceeds occupational limits (TLV value) wear appropriate NIOSH approved air purifying respirator.
Incompatibles:	Acids, strong oxidizers.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Name	ACGIH TLV (ppm)		OSHA Pel (ppm)	
	TWA	STEL	PEL	STEL
Calcium Carbonate	Inhalable dust, 10 (for PNOS) Respirable dust 3 (for PNOS)	N/A	Total dust, 5 Respirable dust, 5	N/A
Kaolin	2mg/m ³ , Respirable	N/A	N/A	N/A
Talc	2 mg/m ³	N/A	N/A	N/A
1, 2 Propanediol	N/A	N/A	N/A	N/A
<i>N/A = Not Available N/E = Not Established</i>				

PROTEK – SAFETY DATA SHEET

Control Parameters:	No TLV data available on product.
Appropriate Engineering Controls:	Use only in well ventilated areas. Exhaust ventilation if used indoors on a continuous basis.
Personal Protective Equipment	
Respiratory Protection:	If exposure cannot be controlled below applicable limits, use the appropriate NIOSH approved respirator such as an air purifying respirator with organic vapour cartridge and dust/mist filter.
Eye Protection:	Use safety glasses, goggles or full face shield where required.
Skin Protection:	Use chemically impervious nitrile or neoprene gloves. Wear long sleeved protective clothing. When required, wear impervious rubber apron. The selection of personal protective equipment and clothing varies, depending upon conditions of use.

SECTION 9: PHYSICAL PROPERTIES

Physical State/Appearance:	Coloured Paste
Odour:	Nearly Odourless
Odour Threshold:	Data Not Available
pH:	7.5 – 9.5
Melting Point:	Data Not Available
Freezing Point:	Data Not Available
Boiling Point:	>100° C
Flash Point (Setaflash Closed Cup):	Data Not Available
Relative Evaporation Rate (Butylacetate=1)	Data Not Available
Flammability (solid, gas):	Data Not Available
Explosive Limit:	Data Not Available
Vapour Pressure:	Data Not Available
Vapour Density:	Data Not Available
Density / Specific Gravity:	1.4 – 1.6
% Volatiles by Weight:	34
Solubility in Water:	Soluble in hot or cold water
Partition Coefficient:	Data Not Available
Auto Ignition Temperature:	Data Not Available
Decomposition Temperature:	Data Not Available
Viscosity:	Data Not Available

SECTION 10: STABILITY AND REACTIVITY

Reactivity:	Avoid contact with incompatibles
Chemical Stability:	Stable at normal condition of usage
Possibility of Hazardous Reactions:	Will not occur.
Conditions to Avoid:	Avoid ignition sources, heat, sparks, open flame, direct sunlight and extremely high or low temperatures.
Incompatibles:	Acids, strong oxidizers. Materials reactive with hydroxyl bearing compounds. Strong bases. Aluminum and its alloys.
Hazardous Decomposition Products:	CO, CO ₂ , hydrocarbons, free chlorine (if burned), oxides of nitrogen, hydrogen chloride. Heating in air may produce irritating aldehydes, acids and ketones.

PROTEK – SAFETY DATA SHEET

SECTION 11: TOXICOLOGICAL INFORMATION

Name	LD 50			LC 50		
	mg/kg	Animal	Route	ppm	Animal	Route
Calcium Carbonate		N/A			N/A	
Kaolin	>5000 >2000	Rat Rabbit	Oral Dermal		N/A	
Talc		N/A			N/A	
1,2 Propanediol	>1000	Rabbit	Dermal		N/A	
N/A = Not Available N/E = Not Established						

- Acute Toxicity:** No test data on mixture.
- No Test Data for the Mixture On:** Skin corrosion/irritation, eye damage/irritation, skin sensitization, respiratory sensitization, germ cell mutagenicity, carcinogenicity, reproductive toxicity, STOT-single exposure, STOT- repeated exposure, aspiration.
- Likely Routes of Exposure:** Inhalation, eye contact, skin contact, ingestion.
- Symptoms/Injuries after Inhalation:** Inhalation of vapour or mist can cause drowsiness, cause damage to lungs, brain and central nervous system. Inhalation of dust from sanding may cause damage to lungs.
- Symptoms/Injuries after Skin Contact:** Direct contact with eyes can cause slight irritation.
- Symptoms/Injuries after Ingestion:** May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

SECTION 12: ECOLOGICAL INFORMATION

Toxicity:	No test data on mixture.
Persistence and Degradability:	No test data on mixture.
Bio-accumulative Potential:	No test data on mixture.
Mobility in Soil:	No test data on mixture.
Other Adverse Effects:	None known.

SECTION 13: DISPOSAL CONSIDERATIONS

- Handling for Disposal:** Handle waste according to recommendations in Section 7. Empty containers retain residue (liquid and/or vapour) and can be dangerous. Do not cut, weld, drill or grind on or near this container.
- Methods of Disposal:** Dispose of in accordance with federal, provincial/state and local hazardous waste laws. Do not discharge into sewage or municipal water. Do not incinerate closed containers.
- RCRA:** If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.

DO NOT INCINERATE CLOSED CONTAINERS.

PROTEK – SAFETY DATA SHEET

SECTION 14: TRANSPORTATION INFORMATION

UN Number:	Non Regulated.
UN Proper Shipping Name:	Non Regulated.
Transport Hazard Class:	Non Regulated.
Packing Group:	Non Regulated.
Environmental Hazards:	Information not available.
Special Precautions for User:	Appropriate advice on safety should accompany the package. Keep away from heat, sparks and open flame. Avoid static electricity.
Transport in Bulk:	Information not available.

SECTION 15: REGULATORY INFORMATION

Canada: All components are in compliance with the Canadian environmental protection act and are present on the domestic substances list. This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the CPR.

USA:

TSCA: All components of this material are on the US TSCA inventory or are exempt.

OSHA: This material is classified as hazardous under OSHA regulation (29CFR 1910.1200).

CERCLA: Reportable quantities (RQ) (40 CFR 117.302). Data not available.

SARA TITLE 111: Sec 302, extremely hazardous substances, 40 CFR 355 - Data not available

SARA TITLE 111: Sec 313, toxic chemical notification, 40 CFR 372 - Data not available

SECTION 16: OTHER INFORMATION

HMIS:	Health 1	Flammability 0	Physical hazard 0
NFPA:	Health 1	Flammability 0	Reactive Instability 0

Issue Date: April 29, 2016

DISCLAIMER

While Microcolor Dispersions believes that the data contained herein are factual and the opinions expressed are those of qualified experts regarding the results of the tests conducted, the information and data contained herein is not to be taken as warranty or representation for which Microcolor Dispersions assumes liability. They are offered solely for your consideration, investigation and verification. Final determination of the suitability of the material for the use contemplated, the manner of use and whether the suggested use infringes any patent is the sole responsibility of the buyer.