

Texturline Varnishes are Urethane modified acrylic based coatings used for protective coats over stable prepared

Product descriptions and uses:

This engineered system can be used as a finish that can be applied on interior surfaces. A typical installation will give protection for plaster with dead flat aspect.

They are a component of a system that can protect and decorate other products in the Texturline product range. It is highly cost effective in producing very resistant or invisible aspects on a variety of surfaces. After correct surface preparation, 1 or 2 thin coats is generally adequate.

Application is done with combination of rollers, brushes and spray equipment.

Application recommendations:

Texturline strongly suggests that all installers follow procedures laid down in our manual (on line) or after taking a program given by one of our approved associate training facilities.

Only fully approved distributors mandated by Texturline will allow you to understand fully and avoid the defects often seen in coatings.

Description of products:

Zero Gloss Varnish is a dead flat coating the film is invisible to the naked eye. Its principal use is over stone effects plasters where the flat aspect of the material is required.

Satin Finish Varnish is ideal for wood veneer floors or furniture coating. Can be pre catalyzed for a more durable coating on cement floors and countertops.

High Gloss Varnish has the same properties as the satin.

Composition:

Texturline Varnish is a hybrid coating using acrylic modified urethane polymer technology combined with to enhance application and shelf life (3 years)

Back

The principle purpose is to create a

barrier against dirt and allow stains to be removed with soap and water. When the material polymerized the varnish will be resistant to chemicals, as well as being more resistant to foot traffic.

Technical Data:

Ingredients: CAS, NA or UN No.

Acrylic

copolymer

emulsion

Proprietary

Surfactant Proprietary

Water 7732 – 18 -5

Coalescing

agent

25265 – 77 – 4

Urethane

acrylic

emulsion

Proprietary

Methyl ophenylphenate

tetra hydrate

Proprietary

VOC 68g per lb 150g per Liter

Packaging

Varnish: pails–gallons–qts US measure

15L – 3.78L – 0.946L

Isocyanate 8fl ozs

Shelf Life

If stored sealed and in a dry atmosphere a 36 month shelf life from the date on the label.

Do not store below 0° or above 40° C or in direct sunlight. If freezing occurs leave for 24 hours at room temperature stir and use. Texturbase is the only plaster protected without glycol from multiple freeze thaws.

Texturline Decorative Finishes ©
Page 73

Varnish continued:
Coverage

The coverage will vary greatly according to the thickness of application. A 0.946L will vary from 100sq. ft. to 150sq. ft. as a sealer for Venetian plaster effect.

Caution

SKIN ABSORPTION: No evidence of harmful effects from available information

EYE CONTACT: May cause irritation

INGESTION: May cause irritation of stomach with abdominal discomfort

FIRST AID: do not rub eyes, immediately flush with clean water. Skin: wash with soap and water Inhalation: move to fresh air if symptoms persist or develop call medical help. DO NOT TAKE INTERNALLY KEEP OUT OF REACH OF CHILDREN. Before using or handling read carefully MSDS sheet.

Surface preparation

We recommend a test area be applied to test for adhesion where a doubt is present.

A common reason for failure is inadequate surface preparation. A careful inspection should be done prior to application for cracks, unsound surfaces and the hygrometry of the substrate.

Before commencing application remove all loose dirt, grease and other contaminants that could prevent adhesion.

General information

The overall area of application should be divided into manageable areas respecting expansion joints, divide up into zones. This is particularly recommended for the less experienced user. Protect adjacent areas and floors, to remove dry product use warm water or mineral spirit, do not rub with abrasives.

Mixing the material will require a few tools: Trowels or spatulas, a heavy duty drill with a squirrel mixer and mud mixer, heavy duty 50 foot extension cord, plastic floor sheets or get the self adhesive rolls of floor protection. A full list of tools can be seen on our web site.